

UNCLASSIFIED

AD NUMBER

AD807311

LIMITATION CHANGES

TO:

Approved for public release; distribution is unlimited. Document partially illegible.

FROM:

Distribution authorized to U.S. Gov't. agencies and their contractors;  
Administrative/Operational Use; FEB 1967. Other requests shall be referred to NASA, Marshall Flight Center, Redstone Arsenal, AL. Document partially illegible.

AUTHORITY

AEDC, USAF ltr, 4 Apr 1973

THIS PAGE IS UNCLASSIFIED

AEDC-TR-66-263

ARCHIVE COPY  
DO NOT LOAN

ag,



# FORCE TESTS OF THE SATURN V LOR AND SATURN 1B/AS-206 CONFIGURATIONS AT MACH NUMBERS 1.5 THROUGH 8

Leroy M. Jenke

ARO, Inc.

This document has been approved for public release  
its distribution is unlimited *Per A. J. Satterly*  
*dated April 73 signed by*  
**February 1967** *William W. Cole*

~~This document is subject to special export controls  
and each transmittal to foreign governments or foreign  
nationals may be made only with prior approval of  
NASA, Marshall Space Flight Center, Redstone Arsenal,  
Alabama.~~

**VON KÁRMÁN GAS DYNAMICS FACILITY  
ARNOLD ENGINEERING DEVELOPMENT CENTER  
AIR FORCE SYSTEMS COMMAND  
ARNOLD AIR FORCE STATION, TENNESSEE**

AEDC TECHNICAL LIBRARY



PROPERTY OF U. S. AIR FORCE  
AEDC LIBRARY  
AF 40(600)1200

# ***NOTICES***

When U. S. Government drawings, specifications, or other data are used for any purpose other than a definitely related Government procurement operation, the Government thereby incurs no responsibility nor any obligation whatsoever, and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise, or in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Qualified users may obtain copies of this report from the Defense Documentation Center.

References to named commercial products in this report are not to be considered in any sense as an endorsement of the product by the United States Air Force or the Government.

FORCE TESTS OF THE SATURN V LOR AND  
SATURN 1B/AS-206 CONFIGURATIONS  
AT MACH NUMBERS 1.5 THROUGH 8

Leroy M. Jenke  
ARO, Inc.

This document has been approved for public release  
its distribution is unlimited.

*Per A. P. Little  
dated 4 April, 73, signed Ray Wilkin  
D. Cole.*

This document is subject to special export controls  
and each transmittal to foreign governments or foreign  
nationals may be made only with prior approval of  
NASA, Marshall Space Flight Center, Redstone Arse-  
nal, Alabama.

## FOREWORD

The work reported herein was done for the Marshall Space Flight Center (MSFC), at the request of the National Aeronautics and Space Administration (NASA) under System 921E, Project 9064.

The results of tests presented were obtained by ARO, Inc. (a subsidiary of Sverdrup & Parcel and Associates, Inc.), contract operator of the Arnold Engineering Development Center (AEDC), Air Force Systems Command (AFSC), Arnold Air Force Station, Tennessee, under Contract AF40(600)-1200. The tests were conducted intermittently within the period from July 22 to October 11, 1966 under ARO Project No. VT1693. The manuscript was submitted for publication on December 7, 1966.

Information in this report is embargoed under the Department of State International Traffic in Arms Regulations. This report may be released to foreign governments by departments or agencies of the U. S. Government subject to approval of NASA, Marshall Space Flight Center, Redstone Arsenal, Alabama, or higher authority within the Department of the Air Force. Private individuals or firms require a Department of State export license.

This technical report has been reviewed and is approved.

James N. McCready  
Major, USAF  
AF Representative, VKF  
Directorate of Test

Leonard T. Glaser  
Colonel, USAF  
Director of Test

**ABSTRACT**

Static force tests were conducted in the 40-in. supersonic and 12-in. hypersonic tunnels of the von Kármán Gas Dynamics Facility on models of the Saturn V LOR and Saturn 1B/AS-206. Data were obtained at Mach numbers 1.5 through 8 at angles of attack from -4 to 13 deg. The Reynolds number, based on the booster diameter, ranged from  $0.24 \times 10^6$  to  $1.67 \times 10^6$ . The results presented show the effects of Mach number and model attitude on the static longitudinal stability and axial-force characteristics.

## CONTENTS

	<u>Page</u>
ABSTRACT . . . . .	iii
NOMENCLATURE . . . . .	vi
I. INTRODUCTION . . . . .	1
II. APPARATUS	
2.1 Wind Tunnels . . . . .	1
2.2 Models . . . . .	2
2.3 Instrumentation . . . . .	2
III. RESULTS AND DISCUSSION . . . . .	5

## TABLE

I. Test Summary . . . . .	4
---------------------------	---

## APPENDIX

## Illustrations

Figure

1. Model Sketches	
a. Saturn V LOR (0.9-percent Scale Model) . . . . .	9
b. Saturn V LOR Fin and Shroud Details (0.9-percent Scale Model) . . . . .	10
c. Saturn V LOR (0.3366-percent Scale Model). . . . .	11
d. Saturn V LOR Fin and Shroud Details (0.3366-percent Scale Model). . . . .	12
e. Saturn 1B/AS-206 Details . . . . .	13
2. Model Installation Photographs	
a. Saturn V LOR (0.9-percent Scale Model) in Tunnel A . . . . .	14
b. Saturn V LOR (0.3366-percent Scale Model) in Tunnel E . . . . .	15
c. Saturn 1B/AS-206 (0.55-percent Scale Model) in Tunnel A . . . . .	16
3. Saturn V LOR Static Longitudinal Stability and Axial-Force Characteristics	
a. Normal-Force Coefficient . . . . .	17
b. Pitching-Moment Coefficient . . . . .	18
c. Forebody Axial-Force Coefficient (with Fins). . . . .	19

<u>Figure</u>	<u>Page</u>
4. Variations with Mach Number of Static Longitudinal Stability and Axial-Force Parameters, Saturn V LOR . . . . .	20
5. Saturn 1B/AS-206 Static Longitudinal Stability and Axial-Force Characteristics	
a. Normal-Force Coefficient . . . . .	21
b. Pitching-Moment Coefficient . . . . .	22
c. Forebody Axial-Force Coefficient (with Fins) . . . . .	23
6. Variations with Mach Number of Static Longitudinal Stability and Axial-Force Parameters, Saturn 1B/AS-206 . . . . .	24

### NOMENCLATURE

A	Reference area (booster cross-sectional area), in. <sup>2</sup> (see Fig. 1)
A <sub>b</sub>	Base area, in. <sup>2</sup> (see Fig. 1)
C <sub>A</sub>	Forebody axial-force coefficient, C <sub>A<sub>T</sub></sub> - C <sub>A<sub>b</sub></sub>
C <sub>A<sub>b</sub></sub>	Base axial-force coefficient, -C <sub>p<sub>b</sub></sub> (A <sub>b</sub> /A)
C <sub>A<sub>T</sub></sub>	Total axial-force coefficient, $\frac{\text{total axial force}}{q_{\infty}A}$
C <sub>m</sub>	Pitching-moment coefficient, pitching moment/q <sub>∞</sub> Ad
C <sub>m<sub>α</sub></sub>	Initial slope of the pitching-moment curve, deg <sup>-1</sup>
C <sub>N</sub>	Normal-force coefficient, normal force/q <sub>∞</sub> A
C <sub>N<sub>α</sub></sub>	Initial slope of the normal-force curve, deg <sup>-1</sup>
C <sub>p<sub>b</sub></sub>	Base pressure coefficient, (p <sub>b</sub> - p <sub>∞</sub> )/q <sub>∞</sub>
d	Booster diameter, in. (see Fig. 1)
M <sub>∞</sub>	Free-stream Mach number
p <sub>b</sub>	Model base pressure, psia
p <sub>0</sub>	Tunnel stilling chamber pressure, psia
p <sub>∞</sub>	Free-stream static pressure, psia
q <sub>∞</sub>	Free-stream dynamic pressure, psia



$Re_d$	Reynolds number based on booster diameter
$T_o$	Tunnel stilling chamber temperature, °F
$x_{cp}$	Center-of-pressure location forward of the moment reference, $C_{m_\alpha}/C_{N_\alpha}$ , calibers
$\alpha$	Angle of attack, deg

## SECTION I INTRODUCTION

Static force tests were conducted in the 40-in. supersonic and 12-in. hypersonic tunnels (Gas Dynamic Wind Tunnels, Supersonic (A) and Hypersonic (E)) of the von Kármán Gas Dynamics Facility (VKF), AEDC, AFSC, to obtain the longitudinal static stability and axial-force characteristics of the Saturn 1B/AS-206 and the current Saturn V Lunar Orbital Rendezvous (LOR) launch configuration.

Data were obtained at Mach numbers from 1.5 to 8 for an angle-of-attack range of -4 to 13 deg and at Reynolds numbers based on the booster diameter, which ranged from  $0.24 \times 10^6$  to  $1.67 \times 10^6$ .

## SECTION II APPARATUS

### 2.1 WIND TUNNELS

Tunnel A is a continuous, closed-circuit, variable density wind tunnel with an automatically driven flexible-plate-type nozzle and a 40- by 40-in. test section. The tunnel operates at Mach numbers from 1.5 to 6 at maximum stagnation pressures from 29 to 200 psia, respectively, and stagnation temperatures up to 300°F ( $M_\infty = 6$ ). Minimum operating pressures are about one-tenth of the maximum at each Mach number.

Tunnel E is an intermittent, variable density wind tunnel with a nozzle formed by contoured throat blocks and manually adjusted flexible plates. The tunnel has a 12- by 12-in. test section and operates at Mach numbers from 5 to 8 at maximum stagnation pressures from 400 to 1600 psia, respectively, and at stagnation temperatures up to about 900°F. Minimum operating pressures are about one-fourth of the maximum.

A description of the tunnels and airflow calibration information may be found in the Test Facilities Handbook\*.

---

\*Test Facilities Handbook (Sixth Edition). "von Kármán Gas Dynamics Facility, Vol. 4." Arnold Engineering Development Center, November 1966.

## 2.2 MODELS

The models were supplied by MSFC. Two models of the Saturn V LOR were provided, a 0.9-percent scale model which was tested at Mach numbers from 1.5 to 6 in Tunnel A and a 0.3366-percent scale model which was tested in Tunnel E at Mach numbers from 5 to 8. The Saturn 1B/AS-206 model was 0.55-percent scale. The models were provided with alternate aft body sections so that data could be obtained on the Saturn V LOR without fins and engine shrouds and on the Saturn 1B/AS-206 without fins. Model details are given in Fig. 1 (Appendix), and photographs of the models installed in the tunnels are given in Fig. 2.

On all tests of the Saturn V LOR 0.9-percent scale model, a boundary-layer trip composed of a 0.1-in. -wide band of No. 40 carborundum grit was located on the escape tower approximately midway between the tip and shoulder of the conical nose. The 0.3366-percent model was tested at Mach 5 with and without a boundary trip composed of a single row of steel balls (0.010-in. -diam) located at approximately the same location on the escape tower as the trip on the 0.9-percent scale model. No effect of the trip was observed; therefore, the data with trips are not presented.

## 2.3 INSTRUMENTATION

Model force measurements were made with six-component, moment-type, strain-gage balances supplied and calibrated by VKF. Before the tests, static loadings in each plane and combined static loadings were applied to each balance which simulated the range of model loadings anticipated for the tests. The ranges of uncertainties listed below correspond to the differences between the applied loads and the values calculated by the balance equations used in the final data reduction. The minimum uncertainties are for loads up to about 10 percent of the maximum applied and are for loadings on the particular component only (no combined loading interaction effects). The maximum uncertainties are for combined loadings. Since the normal force, pitching moment, and axial force were of primary interest, only the uncertainties for these components are presented.

## Saturn V (0.9-percent Scale) - Tunnel A

<u>Balance Component</u>	<u>Design Load</u>	<u>Range of Static Loading</u>	<u>Range of Uncertainties</u>
Normal force, lb	150	$\pm 3$ to $\pm 60$	$\pm 0.02$ to $\pm 0.14$
Pitching moment, in. -lb	760	$\pm 8$ to $\pm 210$	$\pm 0.08$ to $\pm 0.30$
Axial force, lb	75	$\pm 4$ to $\pm 60$	$\pm 0.15$ to $\pm 0.33$

## Saturn V (0.3366-percent Scale) and Saturn 1B (0.55-percent Scale) - Tunnel E

<u>Balance Component</u>	<u>Design Load</u>	<u>Range of Static Loading</u>	<u>Range of Uncertainties</u>
Normal force, lb	25	$\pm 2$ to $\pm 24$	$\pm 0.03$ to $\pm 0.07$
Pitching moment, in. -lb	80	$\pm 8$ to $\pm 75$	$\pm 0.10$ to $\pm 0.25$
Axial force, lb	8	$\pm 1$ to $\pm 6$	$\pm 0.01$ to $\pm 0.07$

## Saturn 1B (0.55-percent Scale) - Tunnel A

<u>Balance Component</u>	<u>Design Load</u>	<u>Range of Static Loading</u>	<u>Range of Uncertainties</u>
Normal force, lb	30	$\pm 2$ to $\pm 20$	$\pm 0.02$ to $\pm 0.06$
Pitching moment, in. -lb	66	$\pm 3$ to $\pm 34$	$\pm 0.03$ to $\pm 0.15$
Axial force, lb	30	$\pm 1$ to $\pm 20$	$\pm 0.01$ to $\pm 0.06$

The balance used for the Tunnel E tests was cooled by a water jacket which extended over the entire length of the balance. The forward end of the Tunnel E sting was also water cooled. Balance temperatures were measured by copper-constantan thermocouples and monitored during all tests.

In Tunnel A, the base pressures were measured with transducers of 15-, 5-, and 1-psid capacity referenced to a near vacuum and are considered accurate to within 0.25 percent of the transducer capacity. In Tunnel E, the base pressures were measured with 5-psid transducers referenced to an independently variable pressure system and are considered accurate to within  $\pm 0.005$  psi.

A summary of the test conditions and configurations tested is given in Table I.

TABLE I  
TEST SUMMARY

Nominal $M_\infty$	Calibrated $M_\infty$	Tunnel	$P_o$ , psia	$T_o$ , °F	$Re_{ft} \times 10^{-6}$	$Re_d \times 10^{-6}$	Saturn V (0.9-percent Scale)		Saturn V (0.3366-percent Scale)		Saturn V (0.55-percent Scale)	
							With Fins	Without Fins	With Fins	Without Fins	With Fins	Without Fins
1.5	1.53	A	13.5	100	3.84	1.14	X	X				
1.5	1.52	A	21.5	100	6.12	0.72					X	X
1.75	1.76	A	23.8	100	6.36	0.75					X	X
2.0	2.00	A	16.0	100	3.84	1.14	X	X				
2.0	2.00	A	28.2	100	6.84	0.81					X	X
2.5	2.49	A	18.7	100	3.60	1.07	X	X				
2.5	2.50	A	29.6	100	5.65	0.66					X	X
3.0	3.00	A	33.1	100	4.80	1.43	X	X				
3.0	2.99	A	29.9	100	4.44	0.52						X
3.5	3.50	A	45.1	100	5.15	1.53	X					
3.5	3.50	A	40.3	100	4.55	0.54						X
4.0	4.02	A	60.3	100	5.15	1.53	X					
5.0	5.03	E	310	220	12.00	1.41					X	X
5.0	5.04	E	328	230	15.00	1.67			X	X		
5.0	5.05	A	115	165	5.15	1.53	X					
6.0	5.91	A	81	165	2.40	0.71	X	X				
6.0	5.99	A	174	165	5.15	0.61					X	X
6.0	6.04	E	270	395	4.80	0.57					X	X
6.0	6.08	E	528	420	8.76	0.97			X	X		
7.0	7.08	E	350	590	3.12	0.37					X	X
7.0	7.12	E	570	625	4.68	0.52			X	X		
8.0	7.77	E	410	825	2.04	0.24					X	X
8.0	7.81	E	575	850	2.76	0.31			X	X		

Note: For the Saturn V model without fins, the shrouds are also removed.

### SECTION III

### RESULTS AND DISCUSSION


Static longitudinal stability and axial-force characteristics for the Saturn V LOR are presented in Figs. 3 and 4. Plots of  $C_N$ ,  $C_m$ , and  $C_A$  versus angle of attack are given in Fig. 3, and summary plots showing the variations with Mach number of  $C_{N_\alpha}$ ,  $C_{m_\alpha}$ ,  $x_{cp}$ , and  $C_{A_{\alpha=0}}$  are given in Fig. 4. Similar results for the Saturn 1B/AS-206 are presented in Figs. 5 and 6.

These results show the decrease in normal force and axial force and the forward shift in the center-of-pressure location obtained when the shrouds and fins are removed from the Saturn V LOR and the fins from the Saturn 1B/AS-206. Pitching moment was essentially unaffected by the configuration change. The decrease in axial force with fins removed was reasonably constant with angle of attack; consequently, these data were not included in Figs. 3c and 5c. It should be noted that for the 0.9-percent scale model at Mach 1.5, the data were obtained with the reflected bow shock impinging on the fins to the extent noted in Fig. 1a.

The summary plots of Figs. 4 and 6 show that the center-of-pressure variations over the complete Mach number range ( $M_\infty = 1.5$  to 8) were within 1.5 calibers (booster diameters) for the Saturn V LOR and about 1.6 calibers for the Saturn 1B/AS-206. These data also show that good agreement was obtained between the results from both tunnels at the Mach numbers ( $M_\infty = 5$  and 6) where repeat data were taken. This is noteworthy in the case of the Saturn V LOR when the difference in the model scales for both tunnels is considered.


It may be noted that the axial-force results for the Saturn V LOR with fins and shrouds removed at the higher Mach numbers (Tunnel E tests) are not included in Fig. 4. It is believed that these data did not match the Tunnel A results because of a small increment in axial force which was produced by the balance cooling water lines (see Fig. 2b), which were not as well shielded from the airstream as for the other model configurations. Figure 4 also shows a noticeable decrease in  $C_{A_{\alpha=0}}$  for the Saturn V LOR vehicle at  $M_\infty = 8$ . This can also be seen in the axial-force results of Fig. 3c, which show a dip in the  $C_A$  curve through  $\alpha = 0$  which is typical of the results obtained when flow separation is present on a body at small angles of attack.

**APPENDIX  
ILLUSTRATIONS**




a. Saturn V LOR (0.9-percent Scale Model)  
 Fig. 1 Model Sketches







b. Saturn V LOR Fin and Shroud Details (0.9-percent Scale Model)  
Fig. 1 Continued




c. Saturn V LOR (0.3366-percent Scale Model)  
Fig. 1 Continued




d. Saturn V LOR Fin and Shroud Details (0.3366-percent Scale Model)  
Fig. 1 Continued



e. Saturn 1B/AS-206 Details  
Fig. 1 Concluded




a. Saturn V LOR (0.9-percent Scale Model) in Tunnel A  
Fig. 2 Model Installation Photographs




A E D C  
19102-66

b. Saturn V LOR (0.3366-percent Scale Model) in Tunnel E  
Fig. 2 Continued




c. Saturn IB/AS-206 (0.55-percent Scale Model) in Tunnel A  
Fig. 2 Concluded




a. Normal-Force Coefficient

Fig. 3 Saturn V LOR Static Longitudinal Stability and Axial-Force Characteristics





b. Pitching-Moment Coefficient  
Fig. 3 Continued



c. Forebody Axial-Force Coefficient (with Fins)  
Fig. 3 Concluded






Fig. 4 Variations with Mach Number of Static Longitudinal Stability and Axial-Force Parameters, Saturn V LOR




a. Normal-Force Coefficient

Fig. 5 Saturn IB/AS-206 Static Longitudinal Stability and Axial-Force Characteristics



b. Pitching-Moment Coefficient  
Fig. 5 Continued



c. Forebody Axial-Force Coefficient (with Fins)  
Fig. 5 Concluded




Fig. 6 Variations with Mach Number of Static Longitudinal Stability and Axial-Force Parameters, Saturn 1B/AS-206

DOCUMENT CONTROL DATA - R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1 ORIGINATING ACTIVITY (Corporate author) Arnold Engineering Development Center, ARO, Inc., Operating Contractor, Arnold Air Force Station, Tennessee		2a REPORT SECURITY CLASSIFICATION <b>UNCLASSIFIED</b>	
		2b GROUP N/A	
3 REPORT TITLE  FORCE TESTS OF THE SATURN V LOR AND SATURN 1B/AS-206 CONFIGURATIONS AT MACH NUMBERS 1.5 THROUGH 8			
4 DESCRIPTIVE NOTES (Type of report and inclusive dates)  N/A			
5 AUTHOR(S) (Last name, first name, initial)  Jenke, Leroy M., ARO, Inc.			
6 REPORT DATE  February 1967		7a TOTAL NO OF PAGES  31	7b NO OF REFS  1
8a CONTRACT OR GRANT NO AF40(600)-1200		9a ORIGINATOR'S REPORT NUMBER(S)  AEDC-TR-66-263	
b PROJECT NO 9064			
c System 921E		9b OTHER REPORT NO(S) (Any other numbers that may be assigned this report)  N/A	
10 AVAILABILITY/LIMITATION NOTICES This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of NASA, Marshall Space Flight Center, Redstone Arsenal, Alabama.			
11 SUPPLEMENTARY NOTES  Available in DDC.		12 SPONSORING MILITARY ACTIVITY NASA, Marshall Space Flight Center, Redstone Arsenal, Alabama	
13 ABSTRACT  Static force tests were conducted in the 40-in. supersonic and 12-in. hypersonic tunnels of the von Kármán Gas Dynamics Facility on models of the Saturn V LOR and Saturn 1B/AS-206. Data were obtained at Mach numbers 1.5 through 8 at angles of attack from -4 to 13 deg. The Reynolds number, based on the booster diameter, ranged from $0.24 \times 10^6$ to $1.67 \times 10^6$ . The results presented show the effects of Mach number and model attitude on the static longitudinal stability and axial-force characteristics.			

This document has been approved for public release  
its distribution is unlimited Per A. J. Letter  
dated 4 April, '72, signed by William  
O. Cole



14 KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
Saturn aerodynamic configurations stability axial-force characteristics supersonic flow hypersonic flow  <i>1. Project Saturn II</i> <i>2. Lunar orbited</i> <i>3. Space vehicles --</i>						

*Rendezvous vehicle (LOR)*  
*19-4*

#### INSTRUCTIONS

1. **ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.

2a. **REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. **GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. **REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. **DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. **AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. **REPORT DATE:** Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. **TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. **NUMBER OF REFERENCES:** Enter the total number of references cited in the report.

8a. **CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. **PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. **ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. **OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (*either by the originator or by the sponsor*), also enter this number(s).

10. **AVAILABILITY/LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those

imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through \_\_\_\_\_."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through \_\_\_\_\_."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through \_\_\_\_\_."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES:** Use for additional explanatory notes.

12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (*paying for*) the research and development. Include address.

13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. **KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.